

Flashlights Unlimited FU-405 Deep Purple Inspection Flashlight



FU-405 Deep Purple Inspection Flashlight Specifications

LED Specifications:
Peak Wavelength: 405nm
Output Bandwidth: 400-410nm
Peak Power Dissipation: 1W
Typical Lifespan: 10,000 hrs

Flashlight Specifications:
Overall Length: 5-7/8 in
Maximum Diameter: 1-3/8 in
Weight (Unloaded): 4.9 oz
Weight (2 x CR123A): 6.1 oz
Weight (1 x 18650): 6.5 oz
Material: Aluminum Alloy
Finish: Hard Anodize, Black
Integrity: Water Resistant
Seals: Dual O-Rings, Both Ends
Lens: Dual-Element Diffuser
Bezel: Crenellated Anti-Roll
Switch: Recessed Tailcap Push-Button
Modes: Momentary & Constant (Click)
Accessories: Lanyard & Holster, Nylon

Included Disposable Batteries:
2 x CR123A Lithium
3.0V, 1300-1500mAh
Typical Continuous Runtime: 6 hrs

Optional Rechargeable Battery:
1 x 18650 Lithium Ion
3.7V, 2000-3000mAh
Typical Continuous Runtime: 6 hrs

FU-405 Deep Purple Inspection Flashlight Operation & Maintenance

Regardless of type, always install batteries with the button (+) end facing toward the lens, and the flat (-) end facing toward the tailcap.

Partially depress the tailcap switch for momentary operation, or press until it clicks for constant operation, click again to turn off. Turn off when changing batteries.

Aim the flashlight toward the surface to be inspected, and then turn on the beam. Wear yellow filter glasses to improve the contrast of defects in the fluorescent coating.

Periodically clean the flashlight and lens with a soft cloth slightly moistened with ordinary window cleaner. Periodically lubricate the tailcap o-ring seals and threads with silicone grease. Do not use hydrocarbon solvents or petrochemical lubricants on any part of the flashlight, damage will result.

FU-405 Deep Purple Inspection Flashlight Safety Precautions

The flashlight emits very intense purple light. Do not look directly into the beam (of this or any other high-intensity flashlight), and avoid strongly reflected exposure.

Keep the flashlight and batteries well away from flames or extreme heat or combustible materials. If handled or recharged incorrectly, lithium batteries can cause fires, explosions, injuries, and death.

Do not attempt to recharge disposable lithium batteries. Do not mix batteries of different types or brands or discharge conditions.

Do not leave lithium ion rechargeable batteries unattended during recharging. Do not use an unprotected lithium ion rechargeable battery. Do not recharge lithium ion batteries in any chargers other than those designed for the specific battery types being used.

FU-405 Deep Purple Inspection Flashlight Limited Warranty

The flashlight is warranted to be free of defects in materials and workmanship for a period of one year from the date of purchase or delivery. Your sole remedy under this warranty is repair or replacement (at our option) of the defective flashlight, if returned to us at the customer's expense during the warranty period. The warranty will be voided if the flashlight or batteries have been damaged or operated improperly. There are no warranties of suitability for a specific application. Flashlights Unlimited will accept no liability whatsoever for any direct or consequential or incidental damages arising from the use or misuse or abuse of the flashlight or any accessory items under any circumstances. Battery and charger items are similarly warranted for a period of 90 days from the date of purchase or delivery.

FU-405 Deep Purple Inspection Flashlight

Designed &
Manufactured
Exclusively For

Flashlights Unlimited
3298 Oakcliff Rd
Doraville GA 30340
Tel 1-770-446-7561
Fax 1-770-446-7604
flashlightsunlimited.com

Inspection Flashlight
Made In China

Operations Guide
Printed In USA

Flashlights Unlimited FU-405 Deep Purple Inspection Flashlight Charger & Batteries



FU-405 Deep Purple Inspection Flashlight Charger & Batteries Specifications

Charger Specifications:

Make & Model: UltraFire WF-139
For: 1 Or 2 Batteries, Independent
Battery Type: 3.7V Lithium Ion Only
Type Numbers: 17670 Or 18650
Battery Holders: 2, Spring-Loaded
Charge Indicators: 2, Red/Green LED
Charge Output: 4.2VDC @ 450mA
AC Input: 120-240VAC, 50-60Hz
AC Connection: Type A, 2 Prong
DC Input: 12-14VDC @ 400mA
DC Connection: Auto Cig Lighter
Safety Certifications: CE & PSE

Battery Specifications:

Make & Model: UltraFire LC-18650
Nominal Voltage: 3.7V
Cut-Off Voltage: 2.5V
High-Limit Voltage: 4.25V
Nominal Capacity: 2400mAh
Minimum Capacity: 2250mAh
Internal Impedance: ≤ 180 milliOhms
Over/Under Protection: Internal PCB
Diameter: 18.3mm ± 0.5 mm
Height: 66.5mm ± 0.5 mm
Typical Approx Weight: 46g
Typical Performance: 90% @ 400 Cycles
Typical Charging Lifespan: >500 Cycles
Manufacturing Standard: ISO9001-2000

FU-405 Deep Purple Inspection Flashlight Charger & Batteries Operation

Fully charge each battery before installing in flashlight. Charger can independently charge one or two batteries simultaneously. Use only the supplied batteries, and do not install any other types.

Pull down bottom spring tab and insert battery with button (+) contact at top of charger and flat (-) contact against bottom spring tab. Never install batteries backwards.

Connect either the 120VAC or 12VDC power cord (never both at once) and connect to an appropriate power source (see at left).

Indicator light will flash red when a battery is charging, and will change to green when battery has been fully charged. Remove each battery promptly after charging has been completed for each one.

FU-405 Deep Purple Inspection Flashlight Charger & Batteries Safety Precautions

Keep the flashlight and batteries well away from flames or extreme heat or combustible materials. If handled or recharged incorrectly, lithium batteries can cause fires, explosions, injuries, and death.

Keep the batteries and charger well away from water or liquids of any kind. Exposure to water may cause fatal electrocution.

Do not attempt to recharge disposable lithium batteries. Do not mix batteries of different types or brands in the charger or flashlight. Do not leave lithium ion rechargeable batteries unattended during recharging. Do not use an unprotected lithium ion rechargeable battery. Do not recharge lithium ion batteries in any chargers other than those designed for the specific battery types being used.

FU-405 Deep Purple Inspection Flashlight Charger & Batteries Limited Warranty

The charger and supplied batteries are warranted to be free of defects in materials and workmanship for a period of ninety days from the date of purchase or delivery. Your sole remedy under this warranty is repair or replacement (at our option) of any defective items, if returned to us at the customer's expense during the warranty period. The warranty will be voided if the flashlight or charger or batteries have been damaged or operated improperly. There are no warranties of suitability for a specific application. Flashlights Unlimited will accept no liability whatsoever for any direct or consequential or incidental damages arising from the use or misuse or abuse of the flashlight or lithium ion batteries or charger or any other accessory items under any circumstances.

FU-405 Deep Purple Inspection Flashlight Charger & Batteries

Packaged &
Distributed By

Flashlights Unlimited
3298 Oakcliff Rd
Doraville GA 30340
Tel 1-770-446-7561
Fax 1-770-446-7604
flashlightsunlimited.com

Charger & Batteries
Made In China

Operations Guide
Printed In USA